UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/668,582	09/23/2003	Alfred Stufflet	I-2-0391.1US	2412
VOLPE AND KOENIG, P.C. DEPT. ICC			EXAMINER	
			MALEK, LEILA	
UNITED PLA 30 SOUTH 17	ZA, SUITE 1600 TH STREET		ART UNIT	PAPER NUMBER
PHILADELPHIA, PA 19103			2611	
			·	
SHORTENED STATUTO	RY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MONTHS		03/06/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

SY
----

	Application No.	Applicant(s)
	10/668,582	STUFFLET ET AL.
Office Action Summary	Examiner	Art Unit
•	Leila Malek	2611
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DOWN - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6). MONTHS from the mailing date of this communication.  If NO period for reply is specified above, the maximum statutory period versions of the statut of th	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tin vill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).
Status		
<ul> <li>1) ☐ Responsive to communication(s) filed on 23 Section 23 ☐ This action is FINAL.</li> <li>2b) ☐ This 3☐ Since this application is in condition for alloware closed in accordance with the practice under Expression 25 Exercises 1.</li> </ul>	action is non-final. nce except for formal matters, pro	
Disposition of Claims		
4) ☐ Claim(s) <u>1-36</u> is/are pending in the application. 4a) Of the above claim(s) is/are withdray 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) <u>1,3,4,6,10-12,14,15,17,21-26,28,29,3</u> 7) ☐ Claim(s) <u>2, 5, 7-9, 13, 16, 18-20, 27, 30, and 3</u> 8) ☐ Claim(s) are subject to restriction and/o	vn from consideration.  1,35 and 36 is/are rejected.  2-34 is/are objected to.	
Application Papers		• •
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 23 September 2003 is/a Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Ex	are: a)⊠ accepted or b)⊡ object drawing(s) be held in abeyance. Se ion is required if the drawing(s) is ob	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the priority documents application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in Applicati rity documents have been receive u (PCT Rule 17.2(a)).	on No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date 07/08/2004.	4) Interview Summary Paper No(s)/Mail D 5) Notice of Informal F 6) Other:	ate

## **DETAILED ACTION**

### **Priority**

1. Applicant's claim for the benefit of a prior-filed application under 35 U.S.C. 119(e) or under 35 U.S.C. 120, 121, or 365(c) is acknowledged.

#### Information Disclosure Statement

2. The information disclosure statement submitted on 07/08/2004 has been considered and made of record by the examiner.

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 23, 25, 26, 31, 35, and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Phillips et al. (hereafter, referred as Phillips) (US 5,859,878), in view of Park et al. (hereafter, referred as Park) (US 6,373,902).

As to claim 23, Phillips discloses a digitally programmable transmit module 102 in a radio device (see Fig. 1) including an analog sub-module and a digital processing sub-module. Phillips further shows (see Fig. 1) that in the programmable common transmit module 102, the analog sub-module 108 and the digital sub-module 110 are connected through a tune bus processor 117. Phillips also shows an antenna interface processor 103 (interpreted as radio interface processor), which has been coupled to the serial tune bus processor 117 (through the analog sub-module). Phillips discloses all the subject

Art Unit: 2611

matters claimed in claim 23, except for a plurality of lookup tables which are indexed by data received from the analog radio module; wherein the data values retrieved from the plurality of lookup tables may be used to generate processed data for controlling the digital module. Park discloses a device for linearizing a transmitter in a digital radio communication system (See the abstract). Park further discloses a plurality of lookup tables (See Fig. 3, blocks 351 and 353, and column 6, lines 5-9), which are indexed (as the I-channel pre-distortion look-up table and Q-channel pre-distortion lookup table) by data received from the analog radio module (See Fig. 3 and column 3, lines 50-57); wherein the serial bus processor receives data from the plurality of lookup tables (See Fig. 2, wherein the baseband filters receive the compensated value from the analog part of the transmitter), and uses data values retrieved from the lookup tables to generate processed data for controlling the digital module (See Fig. 2). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Phillips as suggested by Park to compensate for the non-linearties of the analog signal (See the abstract) and as the result increase the performance of the transmitter.

As to claim 25, Park further discloses that the lookup tables are programmed with data so as to compensate for one or more nonlinearities which may be present in the analog radio module (See column 5, last paragraph, i.e. the signal has been converted to analog before calculating the distortion (therefore the distortions are related to the analog signal).

As to claim 26, Park further discloses that the serial bus processor receives data from the plurality of lookup tables (See Fig. 2, wherein the baseband filters receive the

Application/Control Number: 10/668,582

Art Unit: 2611

compensated value from the analog part of the transmitter), and uses data values retrieved from the lookup tables to generate processed data for controlling the digital module (See Fig. 2).

As to claim 31, Phillips further discloses a clock, coupled to the RIP, for determining the relative timing of external events, and also for controlling the analog radio module (See column 14, lines 35-49).

As to claim 35, Park discloses that the nonlinearities include at least one of AGC (automatic gain control) line voltage as a function of gain, and power level control voltage as a function of power output (See Fig. 3, blocks 217 and 223, and column 6, lines 49-51), whereby the digital module need not be modified to work with the specific characteristics of a given analog radio module (i.e. the analog signal nonlinearities have been compensate before the transmission of signal to the digital module (see Figs. 5 and 6).

As to claim 36, Phillips discloses that the digital module is a time-division-duplex (see column 23, lines 8 and Fig. 1 for duplexing), user-equipment (See column 7, lines 47-55), application-specific-integrated-circuit (ASIC) (see column 14, lines 50-67).

4. Claims 1, 3, 4, 6, 10-12, 14, 15, 17, 21, 22, 24, 28, 29 rejected under 35 U.S.C. 103(a) as being unpatentable over Phillips and Park, further in view of Fischer et al. (hereafter, referred as Fischer) (US 5,768,695).

As to claims 1 and 12, Phillips discloses a digitally programmable transmit module 102 in a radio device, including an analog sub-module and a digital processing sub-module (see Fig. 1). Phillips further shows that in the programmable common

transmit module 102, the analog sub-module 108 and the digital sub-module 110 are connected through a tune bus processor 117. Phillips also shows an antenna interface processor 103 (interpreted as radio interface processor), which has been coupled to the serial tune bus processor 117 (through the analog sub-module). Phillips discloses all the subject matters claimed in claims 1 and 12, except that the radio interface processor includes at least one memory-mapped register. Phillips also does not disclose a plurality of lookup tables which are indexed by data received from the analog radio module, and which are programmed with data so as to compensate for one or more nonlinearities which may be present in the analog radio module, but are not accounted for in the digital module; wherein the serial bus processor receives data from the plurality of lookup tables, and uses data values retrieved from the lookup tables to generate processed data for controlling the digital module. Park discloses a device for linearizing a transmitter in a digital radio communication system (See the abstract). Park further discloses a plurality of lookup tables (See Fig. 3, blocks 351 and 353, and column 6, lines 5-9) which are indexed (as the I-channel pre-distortion look-up table and Qchannel pre-distortion lookup table) by data received from the analog radio module (See Fig. 3 and column 3, lines 50-57), and which are programmed with data so as to compensate for one or more nonlinearities which may be present in the analog radio module (See column 5, last paragraph, i.e. the signal has been converted to analog before calculating the distortion; therefore the distortions are related to the analog signal); wherein the serial bus processor receives data from the plurality of lookup tables (See Fig. 2, wherein the baseband filters receive the compensated value from the

Page 6

Art Unit: 2611

analog part of the transmitter), and uses data values retrieved from the lookup tables to generate processed data for controlling the digital module (See Fig. 2). It would have been obvious to one of ordinary skill in the art at the time of invention to modify Phillips as suggested by Park to compensate for the non-linearties of the analog signal (See the abstract) and increase the performance of the transmitter. Phillips and Park disclose all the limitations claimed in claims 1 and 12, except that the radio interface processor includes at least one memory-mapped register. Fischer, in the same field of endeavor, discloses an apparatus for providing a flexible interface for creating the necessary control signaling of a radio transmitter (see column 1, first paragraph). Fischer, further discloses a radio interface unit 402 (see Fig. 3), which includes a register set 406, which is coupled to the state machine 404 (See column 4, lines 27-39). Since the radio interface unit is a control device, which controls the elements that are connected to it, it would have been obvious to one of ordinary skill in the art at the time of invention to modify the Phillips' radio/antenna interface unit as suggested by Fischer to include the registers inside the radio interface device in order to save the control information of the other units. Fischer is silent in disclosing that the registers are memory-mapped registers, however since the memory-mapped registers have the fastest mechanism for data retrieval (e.g. as evidence by Santos et al. 1), it would have been obvious to one of ordinary skill in the art at the time of invention to use these kind of registers instead of the registers used by Fischer for the reasons stated above.

<sup>&</sup>lt;sup>1</sup> Santos et al. (US 5,933,158, see column 24, first paragraph)

Application/Control Number: 10/668,582

Art Unit: 2611

on outlier realined. To out, or

As to claims 3, 14, and 28 Fischer further discloses that the radio interface unit 402 includes a state machine equipped to access the registers (see Fig. 3). It would have been obvious to one of ordinary skill in the art at the time of invention to use a radio interface unit as suggested by Fischer including a state machine having access to the register sets to provide the appropriate signals to the other parts of the system (see column 5, lines 4-6).

As to claims 4, 15, and 29, Fischer discloses that the radio interface 402 includes a processor interface (the state machine 404 has been interpreted as processor interface) for accessing the register. It would have been obvious to one of ordinary skill in the art at the time of invention to use a radio interface unit as suggested by Fischer including a state machine (or processor interface) having access to the register sets to provide the appropriate signals to the other parts of the system (see column 5, lines 4-6).

As to claims 6 and 17, Phillips further discloses a clock, coupled to the RIP, for determining the relative timing of external events, and also for controlling the analog radio module (See column 14, lines 35-49).

As to claims 10 and 21, Park discloses that the nonlinearities include at least one of AGC (automatic gain control) line voltage as a function of gain, and power level control voltage as a function of power output (See Fig. 3, blocks 217 and 223, and column 6, lines 49-51), whereby the digital module need not be modified to work with the specific characteristics of a given analog radio module (i.e. the analog signal

Art Unit: 2611

nonlinearities have been compensate before the transmission of signal to the digital form) (see Figs. 5 and 6).

As to claim 11 and 22, Phillips discloses that the digital module is a time-division-duplex (see column 23, lines 8 and Fig. 1 for duplexing), user-equipment (See column 7, lines 47-55), application-specific-integrated-circuit (ASIC) (see column 14, lines 50-67).

As to claim 24, Phillips and Park disclose all the limitations claimed in claim 23, except that the radio interface processor includes at least one memory-mapped register. Fischer, in the same field of endeavor, discloses an apparatus for providing a flexible interface for creating the necessary control signaling of a radio transmitter (see column 1, first paragraph). Fischer, further discloses a radio interface unit 402 (see Fig. 3), which includes a register set 406, which is coupled to the state machine 404 (See column 4, lines 27-39). Since the radio interface unit is a control device, which controls the elements that are connected to it, it would have been obvious to one of ordinary skill in the art at the time of invention to modify the Phillips' radio/antenna interface unit as suggested by Fischer to include the registers inside the radio interface device in order to save the control information of the other units. Fischer is silent in disclosing that the registers are memory-mapped registers, however since the memory-mapped registers have the fastest mechanism for data retrieval (e.g. as evidence by Santos et al.), it would have been obvious to one of ordinary skill in the art at the time of invention to use these kind of registers instead of the registers used by Fischer for the reasons stated above.

Application/Control Number: 10/668,582

Art Unit: 2611

# Allowable Subject Matter

5. Claims 2, 5, 7-9, 13, 16, 18-20, 27, 30, and 32-34 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Leila Malek whose telephone number is 571-272-8731. The examiner can normally be reached on 9AM-5:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Mohammad Ghayour can be reached on 571-272-3021. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Leila Malek Examiner Art Unit 2611

L.M

MOHAMMED GHAYOUR SUPERVISORY PATENTLEXAMINER